


BALL AND ROTATING TRUCK



HEIGHT ABOVE GROUND		25ft	30ft	35ft	40ft
OVERALL LENGTH	a	27.5'	33'	39'	44'
BUTT DIAMETER		6"	6.75"	7"	7"
TOP DIAMETER		3"	3"	3"	3"
WALL THICKNESS		1/8"	1/5"	1/5"	1/5"
WEIGHT OF POLE (LBS)		39	60	74	96
YARD ARM LOCATION	f	15'	21.75'	25.5'	29'
YARD ARM LENGTH	b	6'	8'	10'	10'
GROUND SLEEVE DIAMETER		15"	15"	17.5"	17.5"
GROUND SLEEVE DIAMETER		7"	8"	8"	8"
GROUND SLEEVE LENGTH		2.5'	3'	4'	4'
CLEAT LOCATION	c	5'	5'	5'	5'
FOUNDATION DETAIL	d & e	24x36	27X42	27X54	27X54
DIAMETER OF GOLD BALL		5"	6"	6"	6"

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS.
2. DO NOT SCALE DRAWINGS.
3. CONTRACTORS NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info REFERENCE NUMBER 834-002.

